













Sonde Model Frequency   Prod. Number	Image	Mounting & dimensions				Operating distance		Min. diameter of straight duct	Battery		IP / IK codes	Max. ambient pressure
		thread **)	weight	diameter	length	free air	cast iron duct		type	op. time		
<b>NanoSonde</b> <b>MPL4-33</b> 33 kHz   V14010		M3.5 (F)	5 g	4.6 mm	94 mm	2.3 m	0 m	6 mm	BR425	9 h	IP67 / IK02	5 bar (air) 0.5 bar (water)
<b>MicroSonde</b> <b>MPL6-33</b> 33 kHz   V14020		M5 (F)	9 g	6.4 mm	84 mm	2.3 m	0 m	8 mm	BR425	9 h	IP67 / IK04	6 bar (air) 4 bar (water)
<b>MicroSonde</b> <b>VMS6-33</b> 33 kHz   V19010		M5 (F)	14 g	6.4 mm	114 mm	4.7 m	0 m	9 mm	BR535	6 h	IP67 / IK07	6 bar (air) 4 bar (water)
<b>MicroSonde</b> <b>MPL7-33</b> 33 kHz   V14032 *)		M5 (F)	15 g	7.5 mm	114 mm	5.1 m	0 m	10 mm	BR535	6 h	IP67 / IK07	6 bar (air) 4 bar (water)
		M6 (F)										
<b>MiniSonde</b> <b>MPL9-33</b> 33 kHz   V14042 *)		M5 (F)	35 g	9.0 mm	138 mm	5.7 m	0 m	12 mm	BR535	6 h	IP68 / IK08	10 bar
		M6 (F)										
<b>Sonde</b> <b>PL18-33</b> 33 kHz   V14052 *)		M12 (F)	70 g	18 mm	85 mm	10 m	0 m	21 mm	LS14250	20 h	IP68 / IK08	10 bar
		M10 (M) M6 (F)	61 g									
<b>Sonde</b> <b>PL18-05</b> 512 Hz   V14062 *)		M12 (F)	103 g	18 mm	110 mm	6.4 m	4.2 m	21 mm	LS14250	8 h	IP68 / IK08	6 bar
		M10 (M) M6 (F)	94 g									
<b>MegaSonde</b> <b>PL42-05</b> 512 Hz   V14080		M12 (F)	990 g	42 mm	234 mm	16 m	10 m	50 mm	8 x LR6	5 h	IP68 / IK08	6 bar

\*) Product includes one transmitter and two battery compartments with different threads.  
Corresponding products with single battery compartment are discontinued.

\*\*\*) (F) = female thread, (M) = male thread

© H.Vesala Oy 2022-02. Contents subject to change without notice.